

Delock Antenna Cable RP-SMA Plug > RP-SMA Jack CFD400 LLC400 2 m low loss

Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterized by a very low attenuation.



Item no. 13014

EAN: 4043619130146

Country of origin: Taiwan,
Republic of China

Package: White Box

Technical details

- Connectors: RP-SMA plug > RP-SMA jack
- Cable type: CFD400, LLC400
- Impedance: 50 Ohm
- Cable attenuation:
 - 2.4 GHz: ca. 0.22 dB per meter
 - 5.7 GHz: ca. 0.35 dB per meter
- Diameter: ca. 10.5 mm
- Smallest bending radius: 51.5 mm
- Colour: black
- Cable length: ca. 2 m


System requirements

- Device with free RP-SMA connector

Package content

- Antenna cable

Images



Interface

Connector 1:	1 x RP-SMA plug
Connector 2:	1 x RP-SMA jack

Technical characteristics

Impedance:	50 Ω
------------	------

Physical characteristics

Cable type:	CFD400, LLC400
Cable attenuation:	0.22 dB @ 2.4 GHz per meter 0.35 dB @ 5.7 GHz per meter
Cable colour:	black
Cable length:	2 m
Cable diameter:	10.5 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

