

PoweredUSB cable male 24 V > 8 pin male 1 m for POS printers and terminals

Description

This PoweredUSB cable by Delock can be used to connect a device with 8 pin port to a PC or hub with PoweredUSB 24 V port. It is suitable for connecting various POS devices such as printers and terminals, e.g. by Epson, IBM, Wincor or HP. The cable is used both for data transmission and for power supply of the connected device.



Item no. 85477

EAN: 4043619854776

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
1 x PoweredUSB male 24 V >
1 x 8 pin male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge:
26 AWG data line
20 AWG power line
- Cable diameter: ca. 6.5 mm
- Cable double shielded
- Data transfer rate up to 480 Mbps
- Colour: black
- Length incl. connectors (L): ca. 1 m

System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free 8 pin female port

Package content

- PoweredUSB cable

Images



General

Specification:	PoweredUSB
----------------	------------

Interface

Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	1 x 8 pin male

Technical characteristics

Data transfer rate:	USB 2.0 up to 480 Mb/s
Voltage:	24 V

Physical characteristics

Cable gauge:	26 AWG data line 20 AWG power line
Shielding:	double
Length:	1 m
Colour:	black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

