

USB 2.0 to serial RS-232 adapter D-Sub 9 female with compact connector housing 50 cm FTDI

Description

This USB 2.0 Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc.

User-friendly RS-232 plug

The RS-232 connector is characterized by its small dimensions (39.0 x 33.0 x 14.7 mm) and provides a pleasant handling at device connections, cable glands, patch panels, etc.



Item no. 66453

EAN: 4043619664535

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
1 x USB 2.0 Type-A male
1 x serial RS-232 DB9 female with nuts
- Chipset: FTDI FT232R
- Data transfer rate up to 921.6 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bits: 1, 2
- Databits: 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 128 Byte - RX
- FIFO: 256 Byte - TX
- Cable length incl. connectors: ca. 50 cm


System requirements

- Chrome OS
- Linux Kernel 5.15 or above
- Mac OS 12.4 or above
- Windows 10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB 2.0 to 1 x serial adapter
- User manual

Images



General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11

Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x serial RS-232 DB9 female

Technical characteristics

Chipset:	FTDI 232R
Data transfer rate:	921.6 Kbps
FIFO:	128 byte 256 Byte
Data transmission:	asynchronous Bidirectional
UART:	USB to serial UART

Physical characteristics

Cable length:	50 cm
Pin finishing:	gold-plated
Shielding:	double
Colour:	black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de