

Antenna Cable SMA plug > SMA jack CFD/RF200 7.5 m low loss

Description

This high-quality coaxial cable ensures a reliable connection of components of the radio frequency technology. It is characterised by a very low attenuation.



Item no. 89426

EAN: 4043619894260

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Technical details

- Connectors:
1 x SMA plug >
1 x SMA jack
- Cable type: CFD/RF200
- Cable attenuation:
0.55 dB @ 2.4 GHz per meter
0.86 dB @ 5.7 GHz per meter
- Impedance: 50 Ohm
- Colour: black
- Cable diameter: ca. 4.8 mm
- Smallest bending radius: 12.7 mm
- Cable length: ca. 7.5 m


System requirements

- Device with a free SMA connector

Package content

- Antenna cable

Images



Interface

Connector 1:	1 x SMA plug
Connector 2:	1 x SMA jack

Technical characteristics

Impedance:	50 Ω
------------	-------------

Physical characteristics

Cable category:	coaxial
Cable type:	CFD200
Cable attenuation:	0.46 dB @ 1.8 GHz per meter
Cable colour:	black
Cable length incl. connectors:	7.5 m
Smallest bending radius:	12.7 mm
Cable diameter:	4.8 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de

